# 4T4R, 4 x 20 W

## DL 1805 ~ 1880 MHz / UL 1710 ~ 1785 MHz

## Features

- Field Proven Performance and Quality.
- Compact and Light Weight with 4T4R.
- Flexible deployment for different use cases
  : 2T2R for 2 sectors or 4T4R for single sector.



## Technical Specification

| | | |
|---|---|---|
| Frequency Range | 1805 ~ 1880 MHz | 1710 ~ 1785 MHz |
| IBW / OBW (Occupied BW) | 75 MHz / 20 MHz | |
| RF Output Power | 20 W per path | |
| Channel Bandwidth | LTE 5 / 10 / 15 / 20 MHz | |
| Power Supply | - 48 VDC, nominal (- 37 to - 57 VDC) | |
| Fronthaul Interface | 1 port, CPRI rate 7 | |
| AISG (V2.0) | 1 port, AISG v2.0 | |
| Spurious Emission | 3 GPP | |
| Operating Temperature | - 40℃ to + 55℃ | |

## Mechanical Specification

| | |
|---|---|
| Dimension (W × D × H) | 305 x 120 x 400 mm |
| Weight | 12.9 kg (including solar shield & Mount bracket) |
| IP Grade | IP 65 |
| Cooling Method | Natural Convection |
| RF Output Connector | 4.3 - 10 |